

LUPES® TWIST SOFT



019 LUPES® TWIST SOFT



BENEFITS / FEATURES

DOES NOT HARDEN
SOFT HAND
EASY TO SPLICE
CLASSIC LOOK

APPLICATIONS

DOCK LINE

SPECIFICATIONS

MATERIAL	POLYESTER STAPLE FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	3 STRAND PLAIED
UV RESISTANCE	GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	225°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15-20
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGE DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
019	8	5,05	850
019	10	7,55	1.200
019	12	10,10	1.600
019	14	15,10	2.400
019	16	18,90	3.400
019	18	21,40	4.700
019	20	30,25	5.500

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

