

LUPES® LS



KAYA ROPES

UPGRADE YOUR LINES!



207-227 LUPES® LS/MIX



BENEFITS / FEATURES

- EASY TO SPLICE
- DURABLE
- VERY LONG SERVICE LIFE
- HIGH BREAKING LOAD
- SHARES THE LOAD EQUALLY BETWEEN COVER AND CORE
- STRETCHES LESS THAN THE STANDARD POLYESTER

APPLICATIONS

MAIN HALYARD

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: COATED HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<4%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
207-227	6	3,10	1.200
207-227	8	5,25	1.700
207-227	10	8,10	2.560
207-227	12	11,35	3.600

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

