

LUPES® COVER



507 LUPES® FENDER



BENEFITS / FEATURES

GOOD KNOT RETENTION
 SUPPLE SURFACE
 GREAT FOR FENDERS
 EASY HANDLING

APPLICATIONS

FENDER MOORING

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	24-32 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<13%
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGE DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
507	4-6	-	-
507	5-7	-	-
507	6-8	-	-
507	7-10	-	-
507	8-12	-	-

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

