

LUPES® SOFT



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY
EASY TO SPLICE
SUITABLE FOR WINCHES
EXCELLENT GRIP
SUPPLE SURFACE

APPLICATIONS

MAIN SHEET

SEE PAGE 47

SPECIFICATIONS

MATERIAL	COVER: POLYESTER STAPLE FIBER CORE: HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 16-20-24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	SUFFICIENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
011	6	2,70	1.080
011	8	4,10	1.550
011	10	6,65	2.330
011	12	9,50	3.270

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

