

ROCK SOFT- D



BENEFITS / FEATURES

VERY SUITABLE FOR JAMMERS
COMFORTABLE HANDLING
LOW STRETCH
LIGHTWEIGHT
EXCELLENT DINGHY SHEET
HIGH KNOTTED STRENGTH

APPLICATIONS

MAIN SHEET

SPECIFICATIONS

MATERIAL	BLENDED DYNEEMA® SK 78-POLYESTER STAPLE FIBER
SPECIFIC GRAVITY	0,99-1,20 KG/DM ³
CONSTRUCTION	8 PLAITED (HOLLOW BRAID)
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<2%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
205	3	0,57	350
205	4	0,78	550
205	5	1,30	900
205	6	2,05	1.350
205	8	3,65	2.350

***UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)**

