

DYNE K® SBF



405-605 DYNE K® SBF 78/99



BENEFITS / FEATURES

SUPERIOR BENDING FATIGUE (SBF)
EXCELLENT BREAKING LOAD (SK99)
BUOYANT
DURABLE
VERY LOW STRETCH
LIGHTWEIGHT
EASY TO SPLICE
DOES NOT KINK

APPLICATIONS

PARASAILING LINE

SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			SK78 (ART.NO: 405)	SK99 (ART.NO: 605)
405-605	6	2,30	3.750	4.425
405-605	8	4,00	6.600	7.788
405-605	10	6,10	10.400	12.272
405-605	12	8,70	16.600	17.700

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA
ROPESUPGRADE
YOUR
LINES!