

LUPA® ROUND




KAYA ROPES

UPGRADE YOUR LINES!



216 LUPA® ROUND



BENEFITS / FEATURES

- HIGH STRENGTH
- EXCELLENT SHOCK ABSORPTION
- HIGH STRETCH
- DURABLE
- SOFT HAND
- DOES NOT KINK
- EASY TO SPLICE

APPLICATIONS

- DOCK LINE
- ANCHOR LINE
- TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	T
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX.%30-35
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE - ORANGE
STANDARD	-
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B.LOAD (kgf)*
216	8	3,95	1.320
216	10	6,17	2.125
216	12	8,88	3.000
216	14	12,10	4.250
216	16	15,80	5.280
216	18	20,00	6.875
216	20	24,70	8.500
216	22	29,90	10.250
216	24	35,50	12.000
216	26	41,70	14.500
216	28	48,40	17.000
216	30	55,50	19.000
216	32	63,20	21.125
216	36	80,00	27.500
216	40	98,70	34.000
216	48	142,00	48.000
216	56	193,00	68.000
216	64	253,00	84.500
216	72	320,00	110.000
216	80	395,00	129.000
216	88	478,00	152.000
216	96	569,00	183.000

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

