


BENEFITS / FEATURES

ECONOMICALLY PRICED
EASY TO SPLICE
MODERATE ELONGATION
BUOYANT

APPLICATIONS

DOCK LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	A
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	3 STRAND
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	EN ISO 1346
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg / 100 m)	(kgf)*
015	4	0,73	280
015	5	1,13	430
015	6	1,63	600
015	8	2,89	1.080
015	10	4,52	1.625
015	12	6,51	2.265
015	14	8,86	3.225
015	16	11,60	4.310
015	18	14,60	5.350
015	20	18,10	6.500
015	22	21,90	7.740
015	24	26,00	9.060
015	26	30,60	10.500
015	28	35,40	12.900
015	30	40,70	14.600
015	32	46,30	16.400
015	36	58,60	20.100
015	40	72,30	24.300
015	48	104,00	33.700
015	56	142,00	44.600
015	64	185,00	56.800
015	72	234,00	70.200
015	80	289,00	86.000
015	88	350,00	102.000
015	96	417,00	120.000

***UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)**

