



APPLICATIONS

MAIN SHEET


GENOA SHEET

SPI SHEET

SPECIFICATIONS


MATERIAL	COVER: POLYESTER STAPLE FIBER
	INNER COVER: -
	CORE: HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 16-20-24 PLAITED
	CORE: 12 PLAITED
UV RESISTANCE	GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
011	6	2,70	1.080
011	8	4,10	1.550
011	10	6,65	2.330
011	12	9,50	3.270
011	14	13,60	4.370
011	16	17,15	5.630

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY

EASY TO SPLICE

SUITABLE FOR WINCHES

EXCELLENT GRIP

SUPPLE SURFACE

