

008 LUPA® STANDARD



BENEFITS / FEATURES

- HIGH STRENGTH
- EXCELLENT SHOCK ABSORPTION
- HIGH STRETCH
- DURABLE
- SOFT HAND
- DOES NOT KINK

APPLICATIONS

- VESSEL SECONDARY MOORING LINE
- VESSEL GENERAL WORKING LINE
- VESSEL TOW LINE
- VESSEL PENDANT
- TUG SHOCK LINE
- TUG PENDANT
- TRAWL/BRIDLE LINE
- OTHER FISHING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	-
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	COVER : 24-32 PLAITED / CORE : 12-16 PLAITED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX. %30-35
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	ISO 10554
LENGTH	UPON REQUEST

OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
008	8	3,98	1.500
008	10	6,22	2.380
008	12	8,96	3.230
008	14	12,20	4.350
008	16	15,90	5.630
008	18	20,20	7.100
008	20	24,90	8.720
008	22	30,10	10.500
008	24	35,80	13.400
008	26	42,00	15.500
008	28	48,80	17.800
008	30	56,00	20.300
008	32	63,70	22.900
008	36	80,60	28.700
008	40	99,50	35.100
008	48	143,00	50.000
008	56	195,00	68.000
008	64	255,00	89.000
008	72	322,00	112.000
008	80	398,00	138.000
008	88	482,00	167.000
008	96	573,00	198.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

