



408 LUPA® EUROPA



APPLICATIONS

DOCK LINE


ANCHOR LINE

TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	-
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	COVER: 24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX.%30
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
408	24	35,10	12.000
408	28	45,40	16.000
408	32	61,20	21.000
408	36	77,00	25.500
408	40	94,65	30.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

DOES NOT HARDEN

DOES NOT KINK

SUPERIOR SOFT HAND

DURABLE

FLEXIBLE COVER

HIGH BREAKING LOAD

EXCELLENT SHOCK ABSORPTION

