

## GP ROCK D® MIX DP



# KAYA ROPES

## UPGRADE YOUR LINES!

770-772 GP ROCK D® MIX DP 78/99



### APPLICATIONS

MAIN HALYARD  
GENOA HALYARD  
SPI HALYARD  
REEFING LINES  
SPI POLE UPHAUL  
SPI POLE FOREGUY  
GENNAKER TACK-LINE  
ROLLER REEFING LINE

### SPECIFICATIONS

MATERIAL	COVER: %50 DYNEEMA® SK 78 FIBER %50 HIGH TENACITY POLYESTER FIBER CORE: COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,99-1,20 KG/DM <sup>3</sup>
CONSTRUCTION	COVER: 24-32 PLAITED CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			DP78 (ART.NO:770)	DP99 (ART.NO:772)
770-772	8	4,95	4.250	5.200
770-772	10	7,40	6.300	7.600
770-772	12	10,35	9.000	10.800
770-772	14	13,65	12.000	14.250
770-772	16	17,20	15.300	18.250
770-772	18	21,20	19.000	22.500
770-772	20	25,80	23.000	27.250
770-772	22	28,80	26.500	31.500
770-772	24	35,00	30.500	36.500

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



### BENEFITS / FEATURES

GOOD PERFORMANCE IN JAMMERS  
EXCELLENT BREAKING LOAD (SK99)  
EXCELLENT ABRASION RESISTANCE  
LOW STRETCH  
EASY TO SPLICE

Dyneema®

