

## LUPP® ROUND



# KAYA ROPES

## UPGRADE YOUR LINES!

218 LUPP® ROUND



## APPLICATIONS

DOCK LINE  
TOWING LINE

## SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	T
SPECIFIC GRAVITY	0,91 KG/DM <sup>3</sup>
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	EN ISO 1346
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



## BENEFITS / FEATURES

DOES NOT HARDEN  
DOES NOT KINK  
SOFT HAND  
ECONOMICALLY PRICED  
BUOYANT  
EASY TO SPLICE

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
218	20	18,10	6.500
218	22	21,90	7.740
218	24	26,00	9.060
218	26	30,80	10.500
218	28	35,40	12.900
218	30	40,70	14.600
218	32	46,30	16.400
218	34	52,40	18.250
218	36	58,60	20.100
218	38	65,40	22.200
218	40	72,30	24.300
218	42	79,90	26.650
218	44	87,50	29.000
218	46	95,70	31.350
218	48	104,00	33.700
218	52	122,20	39.150
218	56	142,00	44.600
218	60	163,00	50.700
218	64	185,00	56.800
218	72	234,00	70.200
218	80	289,00	86.000
218	88	350,00	102.000
218	96	417,00	120.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

