

LUPA® ROUND



KAYA ROPES

UPGRADE YOUR LINES!



216 LUPA® ROUND



APPLICATIONS

VESSEL SECONDARY MOORING LINE
VESSEL GENERAL WORKING LINE
VESSEL TOW LINE
VESSEL PENDANT
VESSEL STOPPERS
TUG SHOCK LINE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	T
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX. %30-35
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	EN ISO 1140
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
216	12	8,88	3.000
216	18	20,00	6.875
216	24	35,50	12.000
216	30	55,50	19.000
216	36	80,00	27.500

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

HIGH STRENGTH
EXCELLENT SHOCK ABSORPTION
HIGH STRETCH
DURABLE
SOFT HAND
DOES NOT KINK
EASY TO SPLICE

