

VECT COVER



741 VECT COVER

*Vectran*

BENEFITS / FEATURES

- IDEAL FOR PROTECTION AGAINST ABRASION
- EXCELLENT GRIP ON WINCHES
- EASY HANDLING
- GOOD HEAT RESISTANCE

APPLICATIONS

SPECIAL COVER

SPECIFICATIONS

MATERIAL	100% VECTRAN® FIBER
SPECIFIC GRAVITY	1,40 KG/DM ³
CONSTRUCTION	24-32 PLAITED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	500°C
CRITICAL TEMPERATURE	350°C
WORKING STRETCH	<3%
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
741	4-6	-	-
741	5-7	-	-
741	6-8	-	-
741	7-10	-	-
741	8-12	-	-
741	10-16	-	-
741	12-20	-	-

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

