

## LUPES® ROUND



# KAYA ROPES

## UPGRADE YOUR LINES!

217 LUPES® ROUND



## BENEFITS / FEATURES

DURABLE  
EASY TO SPLICE  
DOES NOT KINK  
SOFT HAND

## APPLICATIONS

VESSEL SECONDARY MOORING LINE  
VESSEL GENERAL WORKING LINE  
VESSEL TOW LINE  
VESSEL PENDANT  
VESSEL STOPPERS  
TUG SHOCK LINE  
TUG PENDANT  
FLAG LINE

## SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	T
SPECIFIC GRAVITY	1,38 KG/DM <sup>3</sup>
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15-20
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	EN ISO 1141
LENGTH	100-200 M ORANGE SPOOL OR COIL

## OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
217	8	4,85	1.300
217	10	7,57	2.060
217	12	10,90	2.875
217	14	14,90	3.875
217	16	19,40	5.000
217	18	24,60	6.250
217	20	30,30	8.250
217	22	36,70	10.000
217	24	43,70	11.500
217	26	51,20	13.500
217	28	59,40	17.300
217	30	68,20	17.750
217	32	77,60	20.000
217	36	98,20	25.000
217	40	121,00	33.000
217	48	175,00	46.000
217	56	238,00	62.000
217	64	310,00	80.000
217	72	393,00	100.000
217	80	485,00	123.000
217	88	587,00	148.000
217	96	699,00	175.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

