

LUPES® ROUND



KAYA ROPES

UPGRADE YOUR LINES!

217 LUPES® ROUND



BENEFITS / FEATURES

DURABLE
EASY TO SPLICE
DOES NOT KINK
SOFT HAND

APPLICATIONS

DOCK LINE
ANCHOR LINE
TOWING LINE

SPECIFICATIONS

| | |
|------------------------|---|
| MATERIAL | 100% HT POLYESTER FIBER |
| TYPE | T |
| SPECIFIC GRAVITY | 1,38 KG/DM ³ |
| CONSTRUCTION | 12 STRAND BRAIDED |
| UV RESISTANCE | EXCELLENT |
| CHEMICAL RESISTANCE | GOOD |
| MELTING POINT | 256°C |
| CRITICAL TEMPERATURE | 170°C |
| ELONGATION AT BREAK | APPROX.%15-20 |
| FIBER WATER ABSORPTION | APPROX. %1-2 |
| WET ABRASION | GOOD |
| DRY ABRASION | GOOD |
| COLOUR | BLACK - WHITE - NAVY BLUE - GREY - BLUE |
| STANDARD | - |
| LENGTH | 100-200 M ORANGE SPOOL OR COIL |

OTHER COLOURS ON REQUEST

| ART.NO | DIA | WEIGHT | B.LOAD |
|--------|-----|--------------|---------|
| | (Ø) | (kg / 100 m) | (kgf)* |
| 217 | 8 | 4,85 | 1.300 |
| 217 | 10 | 7,57 | 2.060 |
| 217 | 12 | 10,90 | 2.875 |
| 217 | 14 | 14,90 | 3.875 |
| 217 | 16 | 19,40 | 5.000 |
| 217 | 18 | 24,60 | 6.250 |
| 217 | 20 | 30,30 | 8.250 |
| 217 | 22 | 36,70 | 10.000 |
| 217 | 24 | 43,70 | 11.500 |
| 217 | 26 | 51,20 | 13.500 |
| 217 | 28 | 59,40 | 15.500 |
| 217 | 30 | 68,20 | 17.750 |
| 217 | 32 | 77,60 | 20.000 |
| 217 | 36 | 98,20 | 25.000 |
| 217 | 40 | 121,00 | 33.000 |
| 217 | 48 | 175,00 | 46.000 |
| 217 | 56 | 238,00 | 62.000 |
| 217 | 64 | 310,00 | 80.000 |
| 217 | 72 | 393,00 | 100.000 |
| 217 | 80 | 485,00 | 123.000 |
| 217 | 88 | 587,00 | 148.000 |
| 217 | 96 | 699,00 | 175.000 |

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

