


ELASTIC CORD



BENEFITS / FEATURES

PREMIUM QUALITY RUBBER CORE
DURABLE
HIGH ELONGATION
COMPACT CONSTRUCTION

APPLICATIONS

LEECH LINE

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: ELASTIC RUBBER
SPECIFIC GRAVITY	APPROX. 1,38 KG/DM ³
CONSTRUCTION	COVER: 32 PLAITED, CORE: PARALLEL BRAID
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
021	3	0,75	-
021	4	1,30	-
021	5	2,10	-
021	6	3,00	-
021	8	4,30	-
021	10	8,20	-
021	12	12,00	-

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA
ROPES

UPGRADE
YOUR
LINES!

