

## LUPES® TWIST



# KAYA ROPES

## UPGRADE YOUR LINES!

014 LUPES® TWIST



## BENEFITS / FEATURES

REMAINS FIRM UNDER LOAD  
EASY TO SPLICE  
DURABLE

## APPLICATIONS

OTHER FISHING LINES

## SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	A
SPECIFIC GRAVITY	1,38 KG/DM <sup>3</sup>
CONSTRUCTION	3 STRAND PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15-20
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	EN ISO 1141
LENGTH	100-200 M ORANGE SPOOL OR COIL

## OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
014	4	1,21	325
014	5	1,90	515
014	6	2,73	720
014	8	4,85	1.300
014	10	7,57	2.060
014	12	10,90	2.875
014	14	14,90	3.875
014	16	19,40	5.000
014	18	24,60	6.250
014	20	30,30	8.250
014	22	36,70	10.000
014	24	43,70	11.500
014	26	51,20	13.500
014	28	59,40	12.900
014	30	68,20	17.750
014	32	77,60	20.000
014	36	98,20	25.000
014	40	121,00	33.000
014	48	175,00	46.000
014	56	238,00	62.000
014	64	310,00	80.000
014	72	493,00	100.000
014	80	485,00	123.000
014	88	587,00	148.000
014	96	699,00	175.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

