

## LUPES® ROUND



# KAYA ROPES

## UPGRADE YOUR LINES!

217 LUPES® ROUND



## APPLICATIONS

DOCK LINE  
ANCHOR LINE  
TOWING LINE

## SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	T
SPECIFIC GRAVITY	1,38 KG/DM <sup>3</sup>
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15-20
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	EN ISO 1141
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



## BENEFITS / FEATURES

DOES NOT HARDEN  
DOES NOT KINK  
SOFT HAND  
DURABLE  
HIGH BREAKING LOAD  
EASY TO SPLICE

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
217	20	30,40	8.250
217	22	36,70	10.000
217	24	43,70	11.500
217	26	51,20	13.500
217	28	59,50	15.500
217	30	68,30	17.750
217	32	77,70	20.000
217	34	88,00	22.500
217	36	98,40	25.000
217	38	109,70	29.000
217	40	121,00	33.000
217	42	134,00	36.250
217	44	147,00	39.500
217	46	161,00	42.750
217	48	175,00	46.000
217	52	205,00	54.000
217	56	238,00	62.000
217	60	273,00	71.000
217	64	311,00	80.000
217	72	393,00	100.000
217	80	486,00	123.000
217	88	588,00	148.000
217	96	699,00	175.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

