



237 LUPES® LS WORLD



BENEFITS / FEATURES

- EASY TO SPLICE
- DURABLE
- VERY LONG SERVICE LIFE
- HIGH BREAKING LOAD
- SHARES THE LOAD EQUALLY BETWEEN COVER AND CORE
- STRETCHES LESS THAN THE STANDARD POLYESTER

APPLICATIONS

- MAIN HALYARD
- GENOA HALYARD
- SPI HALYARD
- REEFING LINES
- MAIN SHEET
- GENOA SHEET
- SPI SHEET

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER INNER COVER: - CORE: COATED HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 24 PLAITED CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<4%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	ISO 10547
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
237	6	3,10	1.200
237	8	5,25	1.700
237	10	8,10	2.560
237	12	11,35	3.600
237	14	15,30	4.800
237	16	19,45	6.500
237	18	25,45	8.200
237	20	31,00	10.000
237	22	37,90	12.000
237	24	44,40	14.250

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

TURKEY



USA



UK



GERMANY



ITALY



FRANCE



GREECE



SWISS



HOLLAND



SWEDEN



SPAIN



RUSSIA

