

## LUPA® COVER



308 LUPA® COVER



## BENEFITS / FEATURES

GOOD KNOT RETENTION  
SUPPLE SURFACE  
GREAT FOR FENDERS  
EXCELLENT SHOCK ABSORPTION  
EASY HANDLING

## APPLICATIONS

FENDER MOORING

## SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
SPECIFIC GRAVITY	1,14 KG/DM <sup>3</sup>
CONSTRUCTION	24-32 PLAITED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
WORKING STRETCH	<20%
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS &amp; LARGE DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
308	4-6	-	-
308	5-7	-	-
308	6-8	-	-
308	7-10	-	-
308	8-12	-	-

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

