



017 LUPES® SQUARE


BENEFITS / FEATURES

EASY TO SPLICE
DOES NOT KINK
DURABLE

APPLICATIONS

DOCK LINE
ANCHOR LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	L
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	8 STRAND PLAITED (4X2)
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX. %15-20
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE - BLUE
STANDARD	EN ISO 1141
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B. LOAD (kgf)*
017	8	4,85	1.300
017	10	7,57	2.060
017	12	10,90	2.875
017	14	14,90	3.875
017	16	19,40	5.000
017	18	24,60	6.250
017	20	30,30	8.250
017	22	36,70	10.000
017	24	43,70	11.500
017	26	51,20	13.500
017	28	59,40	15.500
017	30	68,20	17.750
017	32	77,60	20.000
017	36	98,20	25.000
017	40	121,00	33.000
017	48	175,00	46.000
017	56	238,00	62.000
017	64	310,00	80.000
017	72	393,00	100.000
017	80	485,00	123.000
017	88	587,00	148.000
017	96	699,00	175.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

