

LUPA® VIPERA PREMIER



KAYA ROPES

UPGRADE YOUR LINES!

228 LUPA® VIPERA PREMIER




APPLICATIONS

DOCK LINE
ANCHOR LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	-
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	COVER: 32 PLAIED, CORE: 12 PLAIED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX.%30
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
228	30	53,40	19.700
228	32	59,60	22.400
228	34	69,60	25.300
228	36	75,80	28.250
228	38	85,75	31.500
228	40	94,40	34.800
228	42	104,35	38.400
228	44	114,35	42.000
228	46	124,30	46.000
228	48	134,30	50.000
228	56	186,85	67.800

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
DURABLE
SUPERIOR CHAFE COVER
HIGH BREAKING LOAD
EXCELLENT SHOCK ABSORPTION

