

STORM D PRO® MIX DT



KAYA ROPES

UPGRADE YOUR LINES!



392-395 STORM D PRO® MIX DT

APPLICATIONS

MAIN SHEET
GENOA SHEET
SPI SHEET
SPI GUYS
GENNAKER TACK-LINE
BACKSTAYS

SPECIFICATIONS

MATERIAL	COVER: %50 TECHNORA® FIBER %50 DYNEEMA® SK 78 FIBER CORE: COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,99-1,20 KG/DM ³
CONSTRUCTION	COVER: 24-32 PLAITED CORE: 12 PLAITED
UV RESISTANCE	GOOD
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B. LOAD (kgf)*	
			DT78 (ART.NO: 392)	DT99 (ART.NO: 395)
392-395	8	4,55	3.600	4.300
392-395	10	6,65	5.650	6.700
392-395	12	8,90	8.000	9.600
392-395	14	11,70	10.400	12.500
392-395	16	14,45	14.000	16.750
392-395	18	18,20	18.000	21.500
392-395	20	22,25	22.000	26.400
392-395	22	25,80	25.000	30.000
392-395	24	30,05	29.000	34.750

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

GOOD GRIP ON WINCHES
VERY GOOD PERFORMANCE IN JAMMERS
EXCELLENT BREAKING LOAD (SK99)
GOOD HEAT RESISTANCE
EXCELLENT ABRASION RESISTANCE
LOW STRETCH
EASY TO SPLICE

Technora®
The power of Aramid

Dyneema®

