

ROCK STRONG® D PLUS



KAYA ROPES

UPGRADE YOUR LINES!



126 - ROCK STRONG® D-PLUS



BENEFITS / FEATURES

SUPERIOR ABRASION RESISTANCE
EXCELLENT BREAKING LOAD
DURABLE
VERY LOW STRETCH
FIRM AND ROUND
DOES NOT KINK
LIGHTWEIGHT

APPLICATIONS

VESSEL PRIMARY MOORING LINES
TUG MAIN TOW LINES
TUG PENDANTS
SALVAGE ROPES
TRAWL/BRIDLE LINES

SPECIFICATIONS

MATERIAL	COVER : DYNEEMA® SK 75/78 INNER COVER : - CORE : COATED DYNEEMA® SK 75/78
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	COVER : 24 - 32 PLAITED CORE : 12 - 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	ISO 10325
LENGTH	UPON REQUEST

LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (mm) (Ø)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
126	20	22,90	28.000
126	22	27,30	35.000
126	24	32,50	41.000
126	26	39,20	48.000
126	28	45,20	55.000
126	32	57,10	74.000
126	36	71,10	92.000
126	40	86,00	115.000
126	44	101,30	139.000
126	48	125,00	162.000
126	52	147,00	193.000
126	56	169,00	220.000
126	60	191,00	253.000
126	64	221,00	289.000
126	68	248,00	327.000
126	72	278,00	364.000
126	76	313,00	403.000
126	80	340,00	452.000
126	88	401,00	536.000
126	96	480,00	629.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



 Dyneema®

