

TP COVER



742 TP COVER

Technora®
The power of fiber!



BENEFITS / FEATURES

- IDEAL FOR PROTECTION AGAINST ABRASION
- GOOD GRIP ON WINCHES
- EASY HANDLING
- VERY GOOD HEAT RESISTANCE
- VERY GOOD PERFORMANCE IN JAMMERS

APPLICATIONS

SPECIAL COVER

SPECIFICATIONS

MATERIAL	50% TECHNORA® FIBER-50% HT POLYESTER FIBER
SPECIFIC GRAVITY	APPROX. 1,40 KG/DM ³
CONSTRUCTION	24-32 PLAITED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<3%
WET ABRASION	VERY GOOD
DRY ABRASION	VERY GOOD
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
742	4-6	-	-
742	5-7	-	-
742	6-8	-	-
742	7-10	-	-
742	8-12	-	-
742	10-16	-	-
742	12-20	-	-

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

