

DYNE K® LS



KAYA ROPES

UPGRADE YOUR LINES!

406 DYNE K® LS



BENEFITS / FEATURES

- SUPERIOR ABRASION RESISTANCE
- EXCELLENT BREAKING LOAD
- BUOYANT
- DURABLE
- EXTREMELY LOW STRETCH
- LIGHTWEIGHT
- DOES NOT KINK

APPLICATIONS

- SPI SHEET
- SPI GUY
- SPI POLE UPHAUL
- SPI POLE FOREGUY
- BACKSTAYS
- VANG

SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	ISO 10325
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT	B.LOAD (kgf)*
		(kg / 100 m)	SK78 (ART.NO: 406)
406	3	0,75	1.100
406	4	1,26	1.920
406	5	1,92	3.000
406	6	2,75	4.400
406	8	4,80	7.700
406	10	7,30	11.500
406	12	10,45	17.500
406	14	14,00	23.750
406	16	18,00	30.900
406	18	22,80	36.800
406	20	27,80	45.000
406	22	33,70	53.500
406	24	39,70	61.750

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)


