

LUPES® VIPERA PREMIER



KAYA ROPES

UPGRADE YOUR LINES!

210 LUPES® VIPERA PREMIER



APPLICATIONS

DOCK LINE
ANCHOR LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	-
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 32 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
210	30	68,35	19.000
210	32	76,30	21.500
210	34	89,05	24.250
210	36	97,00	27.000
210	38	109,75	30.000
210	40	120,80	33.000
210	42	133,60	36.500
210	44	146,35	40.000
210	46	159,15	43.500
210	48	176,75	47.000
210	56	239,20	63.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
DURABLE
SUPERIOR CHAFE COVER
HIGH BREAKING LOAD

