

GP ROCK D® MIX VP



KAYA ROPES

UPGRADE YOUR LINES!

720-722 GP ROCK D® MIX VP 78/99



BENEFITS / FEATURES

- EXCELLENT GRIP ON WINCHES
- EXCELLENT BREAKING LOAD (SK99)
- GOOD HEAT RESISTANCE
- LOW STRETCH
- EASY TO SPLICE

APPLICATIONS

- MAIN SHEET
- GENOA SHEET
- SPI SHEET
- SPI GUYS
- GENNAKER TACK-LINE
- BACKSTAYS

SPECIFICATIONS

MATERIAL	COVER: %50 VECTRAN® FIBER %50 HIGH TENACITY POLYESTER FIBER CORE: COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,99-1,20 KG/DM ³
CONSTRUCTION	COVER: 24-32 PLAITED CORE: 12 PLAITED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C-256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			VP78 (ART.NO: 720)	VP99 (ART.NO: 722)
720-722	8	4,75	4.250	5.200
720-722	10	7,05	6.300	7.600
720-722	12	10,00	9.000	10.800
720-722	14	13,15	12.000	14.250
720-722	16	16,60	15.300	18.250
720-722	18	20,50	19.000	22.500
720-722	20	24,85	23.000	27.250
720-722	22	27,75	26.500	31.500
720-722	24	33,60	30.500	36.500

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



Vectran®

Dyneema®

