

## LUPP® FILM TWIST



# KAYA ROPES

## UPGRADE YOUR LINES!

022 LUPP® FILM TWIST



## BENEFITS / FEATURES

ECONOMICALLY PRICED  
EASY TO SPLICE  
DOES NOT HARDEN  
BUOYANT  
MODERATE ELONGATION

## APPLICATIONS

GENERAL WORKING LINES  
TUG BARGE TIE-UP LINES  
TUG BARGE AND DREDGE WORKING LINES  
TUG MESSENGER LINES  
TRAWL/BRIDLE LINES  
OTHER FISHING LINES  
PURSE SIENE LINES

## SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FILM FIBER
TYPE	A
SPECIFIC GRAVITY	0,91 KG/DM <sup>3</sup>
CONSTRUCTION	3 STRAND
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	WHITE - AQUA GREEN
STANDARD	EN ISO 1346
LENGTH	200-220 M COIL

## OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
022	8	2,89	1.040
022	10	4,52	1.530
022	12	6,51	2.170
022	14	8,86	2.490
022	16	11,60	3.700
022	18	14,60	4.720
022	20	18,10	5.690
022	24	26,00	7.920
022	28	35,40	10.500
022	32	46,30	13.200
022	36	58,60	16.600

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

