

LUPP® ROUND



KAYA ROPES

UPGRADE YOUR LINES!

216 LUPA® ROUND



BENEFITS / FEATURES

ECONOMICALLY PRICED
EASY TO SPLICE
DOES NOT KINK
DOES NOT HARDEN
BUOYANT
MODERATE ELONGATION
EXCELLENT GRIP

APPLICATIONS

VESSEL SECONDARY MOORING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	T
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	BLACK - WHITE - NAVY BLUE
STANDARD	EN ISO 1346
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm) (Ø)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
218	8	2,90	1.80
218	10	4,52	1.625
218	12	6,51	2.265
218	14	8,86	3.225
218	16	11,60	4.310
218	18	14,60	5.350
218	20	18,10	6.500
218	22	21,90	7.740
218	24	26,00	9.060
218	26	30,60	10.500
218	28	35,40	12.900
218	30	40,70	14.600
218	32	46,30	16.400
218	36	58,60	20.100
218	40	72,30	24.300
218	48	104,00	33.700
218	56	142,00	44.600
218	64	185,00	56.800
218	72	234,00	70.200
218	80	289,00	86.000
218	88	350,00	102.000
218	96	417,00	120.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

