

## LUPES® CORD



607 LUPES® CORD



## BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY  
GREAT VALUE FOR MONEY  
LOW STRETCH

## APPLICATIONS

CONTROL LINE

## SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM <sup>3</sup>
CONSTRUCTION	COVER: 16-20 PLAITED, CORE: PARALLEL BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<5%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS &amp; LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
607	3	0,65	180
607	4	1,20	300
607	5	1,80	460
607	6	2,60	660

\*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA  
ROPESUPGRADE  
YOUR  
LINES!