

LUPP® VIPERA PREMIER



KAYA ROPES

UPGRADE YOUR LINES!

210 LUPP® VIPERA PREMIER



APPLICATIONS

DOCK LINE
TOWING LINE

SEE PAGE 73

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	-
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	COVER: 32 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
238	30	40,50	12.000
238	32	46,60	13.200
238	34	52,55	15.000
238	36	58,10	16.000
238	38	63,45	18.200
238	40	72,25	20.500
238	42	81,05	22.800
238	44	86,40	25.000
238	46	95,20	27.300
238	48	103,95	29.600
238	56	141,05	41.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
SUPERIOR CHAFE COVER
ECONOMICALLY PRICED
BUOYANT

