

GP ROCK D® MIX AP



KAYA ROPES

UPGRADE YOUR LINES!

730-732 GP ROCK D® MIX AP 78/99



BENEFITS / FEATURES

- GOOD GRIP ON WINCHES
- EXCELLENT PERFORMANCE IN JAMMERS
- EXCELLENT BREAKING LOAD (SK99)
- VERY GOOD HEAT RESISTANCE
- LOW STRETCH
- EASY TO SPLICE

APPLICATIONS

- MAIN SHEET
- GENOA SHEET
- SPI SHEET
- SPI GUYS
- GENNAKER TACK-LINE
- BACKSTAYS


SPECIFICATIONS

MATERIAL	COVER: %50 KEVLAR® FIBER
	%50 HIGH TENACITY POLYESTER FIBER
SPECIFIC GRAVITY	CORE: COATED DYNEEMA® SK 78/99
	0,99-1,20 KG/DM³
CONSTRUCTION	COVER: 24-32 PLAITED
	CORE: 12 PLAITED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C-256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			AP78 (ART.NO: 730)	AP99 (ART.NO: 732)
730-732	8	4,70	4.250	5.200
730-732	10	6,95	6.300	7.600
730-732	12	9,90	9.000	10.800
730-732	14	13,00	12.000	14.250
730-732	16	16,35	15.300	18.250
730-732	18	20,20	19.000	22.500
730-732	20	24,50	23.000	27.250
730-732	22	27,40	26.500	31.500
730-732	24	33,15	30.500	36.500

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



Dyneema® KEVLAR®

