

DYNE K® WINCHLINE



KAYA ROPES

UPGRADE YOUR LINES!



APPLICATIONS

WINCHLINE
ATV WINCHLINE

SPECIFICATIONS


MATERIAL	COATED DYNEEMA® SK 78/90/99
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	ISO 10325
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGE DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT		B.LOAD (kgf)*
		(kg/25m)**	(kg/30m)**	
035 006	6	1,35	1,50	3.500
035 008	8	1,80	2,00	6.000
035 010	10	2,40	2,70	9.200
035 012	12	3,16	3,60	13.200

*SPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

** THIMBLE & HOOK INCLUDED IN THE WEIGHT



BENEFITS / FEATURES

EXCELLENT BREAKING LOAD (SK99)
BUOYANT
DURABLE
EXTREMELY LOW STRETCH
LIGHTWEIGHT
DOES NOT KINK

