



109 LUPP® VIPERA



BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
FLEXIBLE COVER
ECONOMICALLY PRICED
BUOYANT

APPLICATIONS

DOCK LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	-
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	COVER: 16-20-24 PLAITED, CORE: 16 PLAITED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
109	8	2,90	1.000
109	10	4,20	1.510
109	12	6,20	2.100
109	14	9,10	3.000
109	16	10,90	4.000
109	18	14,50	4.975
109	20	18,15	6.045
109	22	21,75	7.200
109	24	25,90	8.425
109	26	30,35	9.765
109	28	34,95	12.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

