



017 LUPES® SQUARE


**APPLICATIONS**

DOCK LINE  
ANCHOR LINE  
TOWING LINE

**SPECIFICATIONS**

<b>MATERIAL</b>	100% HT POLYESTER FIBER
<b>TYPE</b>	L
<b>SPECIFIC GRAVITY</b>	1,38 KG/DM <sup>3</sup>
<b>CONSTRUCTION</b>	8 STRAND PLAITED (4X2)
<b>UV RESISTANCE</b>	EXCELLENT
<b>CHEMICAL RESISTANCE</b>	GOOD
<b>MELTING POINT</b>	256°C
<b>CRITICAL TEMPERATURE</b>	170°C
<b>ELONGATION AT BREAK</b>	APPROX. %15-20
<b>FIBER WATER ABSORPTION</b>	APPROX. %1-2
<b>WET ABRASION</b>	GOOD
<b>DRY ABRASION</b>	GOOD
<b>COLOUR</b>	WHITE-NAVY BLUE -BLACK
<b>STANDARD</b>	EN ISO 1141
<b>LENGTH</b>	100-200 M PLASTIC/WOODEN SPOOL OR COIL

**OTHER COLOURS ON REQUEST**

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
017	12	10,90	2.875
017	14	14,90	3.875
017	16	19,40	5.000
017	18	24,60	6.250
017	20	30,40	8.250
017	22	36,70	10.000
017	24	43,70	11.500
017	26	51,20	13.500
017	28	59,50	15.500
017	30	68,30	17.750
017	32	77,70	20.000
017	34	88,00	22.500
017	36	98,40	25.000
017	38	109,70	29.000
017	40	121,00	33.000

**\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)**


**BENEFITS / FEATURES**

DOES NOT HARDEN  
DOES NOT KINK  
SOFT HAND  
DURABLE  
HIGH BREAKING LOAD  
EASY TO SPLICE

