



005-505 DYNE K® 78/99



BENEFITS / FEATURES

- SUPERIOR ABRASION RESISTANCE
- EXCELLENT BREAKING LOAD (SK99)
- BUOYANT
- DURABLE
- VERY LOW STRETCH
- LIGHTWEIGHT
- EASY TO SPLICE
- DOES NOT KINK

APPLICATIONS

- SPI POLE UPHAUL
- SPI POLE FOREGUY
- BACKSTAYS
- VANG
- CUNNINGHAM
- MAIN OUTHAUL


SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	ISO 10325
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			SK78 (ART.NO: 005)	SK99 (ART.NO: 505)
005-505	2	0,25	425	502
005-505	3	0,50	950	1.121
005-505	4	0,95	1.650	1.947
005-505	5	1,50	2.600	3.068
005-505	6	2,30	3.750	4.425
005-505	8	4,00	6.600	7.788
005-505	10	6,10	10.400	12.272
005-505	12	8,70	15.000	17.700
005-505	14	11,70	20.400	24.072
005-505	16	15,10	26.520	31.294
005-505	18	19,00	31.620	37.312
005-505	20	23,20	38.760	45.737
005-505	22	28,10	45.900	54.162
005-505	24	33,10	53.000	62.540

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



Dyneema®

