

LUPES® WAX



KAYA ROPES

UPGRADE YOUR LINES!



020 LUPES® WAX



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY
HIGH BREAKING LOAD
EASY TO SPLICE

APPLICATIONS

PARASAILING LINE

SPECIFICATIONS

MATERIAL	COVER: HT WAXED POLYESTER FIBER CORE: HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 16 PLAITED, CORE: 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
020	9	7,50	1.820
020	10	9,05	2.330
020	11	10,70	2.630
020	12	12,70	3.270

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

