

DYNE K® SHACKLE



BENEFITS / FEATURES

SHACKLES ARE LOADED TO 1/2 OF ITS BREAKING STRENGTH

BUOYANT

VERY LOW STRETCH

LIGHT SHACKLES ARE MADE OUT OF DYNEEMA®

APPLICATIONS

WINCH SHACKLE

SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	ISO 10325
LENGTH	-

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	SHACKLE	B.LOAD	SWL	LENGTH
	DIA (Ø)	(kgf)*	(kgf)*	CM
305	4	855	478	8,50
305	6	1.150	575	9,50
305	8	2.340	1.170	11,00
305	10	3.375	1.688	11,50
305	12	4.670	2.375	12,50
305	14	5.980	2.990	15,00
305	18	9.380	4.690	17,50

*SPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA
ROPES

UPGRADE
YOUR
LINES!

