


LUPES® SOLID



BENEFITS / FEATURES

EASY HANDLING
VERY STABLE ROUND CROSS-SECTION

APPLICATIONS

LUFF LINE/LEECH LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	SOLID BRAID (12 PLAITED)
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
117	3	0,75	130
117	4	1,15	220
117	5	1,50	330
117	6	2,25	450
117	8	3,75	780

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

