

LUPES® PLAIN



206 LUPES® PLAIN



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY
EASY TO SPLICE
GREAT VALUE FOR MONEY
DURABLE
VERY LONG SERVICE LIFE

APPLICATIONS

MAIN SHEET

SEE PAGE 47

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
206	6	3,15	1.080
206	8	5,30	1.550
206	10	8,20	2.330
206	12	11,45	3.270

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

