

DYNE K®



KAYA ROPES

UPGRADE YOUR LINES!



005-505 DYNE K® 78/99



BENEFITS / FEATURES

SUPERIOR ABRASION RESISTANCE
EXCELLENT BREAKING LOAD (SK99)
BUOYANT
DURABLE
VERY LOW STRETCH
LIGHTWEIGHT
EASY TO SPLICE

APPLICATIONS

MAIN HALYARD

SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			SK78 (ART.NO: 005)	SK99 (ART.NO: 505)
005-505	2	0,25	425	502
005-505	3	0,50	950	1.121
005-505	4	0,95	1.650	1.947
005-505	5	1,50	2.600	3.068
005-505	6	2,30	3.750	4.425
005-505	8	4,00	6.600	7.788

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

