

## GP ROCK V®



# KAYA ROPES

## UPGRADE YOUR LINES!



## APPLICATIONS

MAIN HALYARD  
GENOA HALYARD  
MAIN SHEET  
SPI GUYS  
CUNNINGHAM  
MAIN OUTHAUL

## SPECIFICATIONS


MATERIAL	COVER: HT POLYESTER FIBER INNER COVER: - COATED: VECTRAN® FIBER
SPECIFIC GRAVITY	APPROX. 1,38 KG/DM <sup>3</sup>
CONSTRUCTION	COVER: 24-32 PLAITED CORE: 12 PLAITED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
101-111	8	5,75	3.400
101-111	10	7,85	5.100
101-111	12	11,20	7.250
101-111	14	14,75	9.000
101-111	16	19,50	11.900
101-111	18	24,20	14.500
101-111	20	29,20	18.000
101-111	22	32,75	21.000
101-111	24	38,50	25.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



## BENEFITS / FEATURES

GOOD PERFORMANCE IN JAMMERS  
HIGH BREAKING LOAD  
EXTREMELY LOW STRETCH  
EASY TO SPLICE

Vectran™

