

LUPES® LS



KAYA ROPES

UPGRADE YOUR LINES!

207 LUPES® LS



227 LUPES® LS MIX



APPLICATIONS

MAIN HALLYARD
GENOA HALLYARD
SPI HALLYARD
REEFING LINES
MAIN SHEET
GENOA SHEET
SPI SHEET

SPECIFICATIONS

MATERIAL	COVER : HT POLYESTER FIBER INNER COVER : - CORE : COATED HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER : 24 - 32 PLAITED CORE : 12 - 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<4%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	ISO 10547
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B.LOAD (kgf)*
207 - 227	6	2,87	1.200
207 - 227	8	5,10	1.700
207 - 227	10	7,97	2.560
207 - 227	12	11,50	3.600
207 - 227	14	15,60	4.800
207 - 227	16	20,40	6.500
207 - 227	18	25,80	8.200
207 - 227	20	31,90	10.000

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY
HIGH BREAKING LOAD
EASY TO SPLICE
DOES NOT KINK
SHARES THE LOAD EQUALLY BETWEEN
COVER AND CORE
STRETCHES LESS THAN THE STANDARD
POLYESTER

