

STORM D PRO



302 STORM D PRO



312 STORM D PRO MIX



APPLICATIONS

MAIN HALYARD
GENOA HALYARD
SPI HALYARD
REEFING LINES
MAIN SHEET
GENOA SHEET
SPI SHEET
SPI GUYS

SPECIFICATIONS

MATERIAL	COVER : HT POLYESTER FIBER INNER COVER : - CORE : COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,99 - 1,20 KG/DM ³
CONSTRUCTION	COVER : 24 - 32 PLAITED CORE : 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	147°C - 256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	GOOD
DRY ABRASION	GOOD
STANDARD	-
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B.LOAD (kgf)*
302 - 312	8	4,30	3.600
302 - 312	10	6,30	5.650
302 - 312	12	9,50	7.700
302 - 312	14	12,20	10.400
302 - 312	16	15,40	13.300
302 - 312	18	19,40	16.600
302 - 312	20	24,00	22.000
302 - 312	22	28,00	25.000
302 - 312	24	33,00	27.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

VERY SUITABLE FOR WINCHES
HIGH BREAKING LOAD
LOW STRETCH
MAXIMUM SERVICE LIFE
VERY STABLE CROSS-SECTION

