

LUPES® CORD



607 LUPES® CORD



BENEFITS / FEATURES

DOES NOT HARDEN
SOFT HAND
LOW STRETCH

APPLICATIONS

LUFF LINE / LEECH LINE

SPECIFICATIONS

MATERIAL	COVER : HT POLYESTER FIBER CORE : HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER : 16-20-24 PLAITED, CORE : 12-16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg / 100 m)	(kgf)*
607	2	0,32	90
607	2,5	0,50	125
607	3	0,72	180
607	4	1,27	310
607	5	2,00	480
607	6	2,87	680

*UNSPLICED BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

