



004 VECT K®

APPLICATIONS

SPI POLE UPHAUL

SPI POLE FOREGUY

VANG

CUNNINGHAM

MAIN OUTHAUL

SPECIFICATIONS

MATERIAL	COATED VECTRAN® FIBER
SPECIFIC GRAVITY	1,40 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	POOR
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	300°C
CRITICAL TEMPERATURE	200°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	APPROX. %1
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
004	3	0,85	800
004	4	1,45	1.500
004	5	2,30	2.000
004	6	3,15	3.000
004	8	5,70	5.000
004	10	9,10	7.500
004	12	13,05	10.200
004	14	18,15	13.000
004	16	22,70	18.750
004	18	27,20	22.500
004	20	36,30	28.000
004	22	40,80	32.000
004	24	45,35	38.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

NO CREEP UNDER CONSTANT LOADS

HIGH BREAKING LOAD

EXTREMELY LOW STRETCH

IDEAL FOR STEERING SYSTEM

EASY TO SPLICE

PERFECT FOR STATIC APPLICATION

PU COATING FOR IMPROVED PROTECTION
AGAINST ABRASION

Vectran®

