

LUPES® TWIST + WIRE C



KAYA ROPES

UPGRADE YOUR LINES!

114 LUPES® TWIST + WIRE C



APPLICATIONS

TRAWL/BRIDLE LINES

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER + 6x7 GALVANIZED WIRE ROPE
TYPE	A
SPECIFIC GRAVITY	-
CONSTRUCTION	3+1 STRAND PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%4-5
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	WHITE
STANDARD	-
LENGTH	UPON REQUEST

OTHER COLOURS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT**	B.LOAD *
	(Ø)	(kg / 100 m)	(kgf)
114	30	98 (WITH 8 MM 6x7 WIRE ROPE)	-
114	32	109 (WITH 8 MM 6x7 WIRE ROPE)	-
114	32	122 (WITH 10 MM 6x7 WIRE ROPE)	-

**THE WEIGHT MAY VARY AROUND ±5 DUE



BENEFITS / FEATURES

QUICK SINK RATE
EASY TO SPLICE
DURABLE

